ELEMENT™ 3" HALOGEN LOW-PROFILE ADJUSTABLE DOWNLIGHT

1 YEAR

The ELEMENT 3" series small aperture, low-profile adjustable downlight provides a unique architectural appearance for shallow ceiling plenum installations. Designed with a shallow 4" housing while utilizing the same trim pieces as the rest of the ELEMENT 3" series, the presence of the Low-Profile version is completely undetectable from below the ceiling. This makes it ideal for space constrained environments such as elevators and healthcare soffits. Complete adjustability allows for lockable hot aiming including 0°-35° tilt and 361° rotation, eliminating deadspots. Wood ceiling option allows for a smooth, flangeless appearance using any flangeless trim.

- Lockable hot aiming including 0°-40° tilt and 361° rotation
- Flangeless wood ceiling option accommodates variable ceiling thickness
- Accepts 2 optical controls and an optional trim mounted lens
- Compatible with LED MR16 replacement lamp. LED MR16 requires no load electronic transformer (12 watt max).
- · Power supplies can be accessed through the aperture
- · Glare reducing snoot integrated
- Lensed and shower options include Solite™ soft focus lens at aperture

Installation


- Includes adjustable hanger bars. Includes butterfly brackets that attach to the side of the housing and are vertically adjustable with a wing nut.
- · Incorporates integral gunsights for positioning with laser level or string

SPECIFICATIONS

LAMP	Low-voltage Halogen MR16 lamp. Compatible with LED MR16 replacement lamps
WATTS	Halogen: 50w Non-IC only
VOLTAGE	120V or 277V
DIMMING*	ELV or MLV (Dimming dependent on transformer type)
ADJUSTABILITY	Hot aiming, including 0°-40° Tilt and 361° rotation
CEILING APPEARANCE	Flanged (Accommodates up to 2.5" drywall ceiling thickness, depending on trim) or Flangeless
CEILING APERTURE	3-7/8"
HOUSING	Non-IC Airtight
	Non-ic Airtigitt
POWER SUPPLY	Halogen: Electronic or Magnetic transformer. No load transformer required for LED MR16 compatibility.
	Halogen: Electronic or Magnetic transformer. No load transformer required for LED MR16
POWER SUPPLY	Halogen: Electronic or Magnetic transformer. No load transformer required for LED MR16 compatibility.
POWER SUPPLY GENERAL LISTING	Halogen: Electronic or Magnetic transformer. No load transformer required for LED MR16 compatibility. ETL listed. Damp listed. Shower version wet listed. Housing: Heavy gauge cold rolled steel
POWER SUPPLY GENERAL LISTING CONSTRUCTION	Halogen: Electronic or Magnetic transformer. No load transformer required for LED MR16 compatibility. ETL listed. Damp listed. Shower version wet listed. Housing: Heavy gauge cold rolled steel Trims: Die-cast aluminum Housing: Black Trims: Antique Bronze, Black, Satin Nickel,

^{*}See ELEMENT-lighting.com for dimmer compatibility.

Includes integral junction box approved for branch circuit through wiring.



shown in flangeless bevel square

^{**}Visit ELEMENT-lighting.com for specific warranty limitations and details.

ELEMENT 3" HALOGEN LOW-PROFILE ADJUSTABLE DOWNLIGHT

GRIDS

HOUSING

PRODUCT SERIES	CEILING APPEARANCE	LAMP	FUNCTION	HOUSING RATING	TRANSFORMER	WATTAGE RESTRICTION (PER SOCKET)	VOLTAGE
E3R ELEMENT 3" ROUND E3S ELEMENT 3" SQUARE	LF FLANGELESS FF FLANGED WC WOOD CEILING**	-H HALOGEN (50 WATT MAX)	A ADJUSTABLE	S SHALLOW NON-IC AIRTIGHT	 E ELECTRONIC M MAGNETIC R REMOTE N NO LOAD ELECTRONIC 	NONE (LEAVE BLANK) -WR WATTAGE RESTRICTION*	120 VOLT (LEAVE BLANK) 240 240 VOLT 277 277 VOLT
		-H	Α	S			

TRIM

PRODU	CT SERIES	CEILING APPEARANCE			TRIM STYLE		APERTURE		FINISH		
	EMENT 3" ROUND EMENT 3" SQUARE	F20	FLANGELESS UP TO 1" CEILING THICKNESS FLANGED UP TO 1" CEILING THICKNESS FLANGED 1.1"-1.5" CEILING THICKNESS FLANGED 1.6"-2.0" CEILING THICKNESS FLANGED 2.1"-2.5" CEILING THICKNESS	_	BEVEL FLAT	_	NO LENS SHOWER LENSED	B S	ANTIQUE BRONZE BLACK SATIN NICKEL WHITE		
						-					

WOOD CEILING OPTION ACCOMMMODATES FLANGELESS TRIMS ONLY.

	\Box	\cap	ı	ı		\cap	Г	П	\	ı		\cap	
\vdash	\vdash	(١. ا	П	-			ш	1	л	ь.	())

FIXTURE TYPE & QUANTITY	JOB NAME & INFO	NOTES

TECH LIGHTING

VISUAL COMFORT & CO.

7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500


TRIMS ARE REQUIRED AND MUST BE ORDERED SEPARATELY.

*TO INCLUDE WATTAGE RESTRICTION LABEL, SPECIFY -WR AT THE END OF THE HOUSING ITEM NUMBER AND SPECIFY WATTAGE (EXAMPLE: -WR37).


**WOOD CEILING OPTION ACCOMMODATES FLANGELESS TRIMS ONLY. ROUND NOT AVAILABLE WITH MAGNETIC TRANSFORMER.

ELEMENT 3" HALOGEN


TRIMS



3" HOUSING







ELEMENT™ 3" HALOGEN LOW-PROFILE ADJUSTABLE DOWNLIGHT

WOOD CEILING OPTIONS / FLANGELESS TRIMS

ROUND



FLANGELESS BEVEL (ANTIQUE BRONZE)



FLANGELESS BEVEL (SATIN NICKEL)



BLACK



FLANGELESS FLAT (ANTIQUE BRONZE)



FLANGELESS FLAT (SATIN NICKEL)



SATIN NICKEL



FLANGELESS BEVEL (ANTIQUE BRONZE)



FLANGELESS BEVEL (SATIN NICKEL)






FLANGELESS FLAT (ANTIQUE BRONZE)



FLANGELESS FLAT (SATIN NICKEL)


ADJUSTABLE TRIM ADAPTER




Wood ceiling housings ("WC" designation in the ordering grid) ship with an adjustable trim adapter that inserts into the housing aperture and allows standard ELEMENT 3" flangeless trims to achieve a truly flangeless, flush ceiling appearance in special applications such as wood or stone installation. For use in new construction.

Consult installation instructions regarding plenum requirements and ceiling thickness ratios.

TRIM ADAPTER INSTALLED



ADAPTER FLUSH



ADAPTER EXTENDED