MERGE[™] 90 DEGREE L CONNECTOR RECESSED TRACK





The continuous line aesthetic created by the ELEMENT Merge recessed track system is enhanced using a specifically engineered 90° turn connector. ELEMENT Merge recessed track can be designed to seamlessly make 90° same-plane turns for enhanced design interest while also allowing the option to add spot heads for accent and task lighting, all without adding more light fixtures to the space.

Pristine design and features:

- Option to add spot heads for accent and task lighting
- Low profile design for use in 2x6 construction

Flanged option is field paintable

SPECIFICATIONS

| VOLTAGE | 120V or 277V (Concealed 10 gauge, low-voltage bus bar, order 12-volt remote transformer sold separately) |
|--------------------|--|
| CEILING APERTURE | 3" beveled |
| CEILING APPEARANCE | Flanged or Flangeless |
| HOUSING | IC Airtight (IC suitable up to R60 spray foam insulation) |
| TRANSITIONS | Seamlessly make 90° (same plane) turns for enhanced design |
| GENERAL LISTING | ETL |
| CONSTRUCTION | Housing: 20 gauge sheet metal Extrusion: Aluminum |
| HARDWARE | Steel |
| FINISH | White Powder Coat |
| WARRANTY* | 1 Year* |




MERGE shown flanged

*Visit ELEMENT-lighting.com for specific warranty limitations and details.


Notes: Typical max run length is 40' for the low-voltage bus which can be powered from both sides for a total of 80'; system wattage will impact max run length

MERGE[™] 90 DEGREE L CONNECTOR RECESSED TRACK

DIMENSIONS



Flanged 90° L connector (top view)



Flangeless 90° L connector (top view)

GRIDS

(II).

CONNECTOR/TRANSITION

| SYSTEM | ТҮРЕ | OUTPUT | CEILING APPEARANCE | FINISH |
|--------|--|-------------------------------|---|---------------|
| RLS3 | L "L" CONNECTOR LPF "L" CONNECTOR WITH POWER FEED [†] | 0 NO INDIRECT - 12V BUS ONLY* | RF RECESSED FLANGED RL RECESSED FLANGELESS | W MATTE WHITE |
| RLS3 | _ | 0 | | VV |

*TRANSFORMER REQUIRED TO ENERGIZE THE LOW-VOLTAGE BUS. [†]*CLOSED* CONFIGURATIONS REQUIRE CONNECTOR WITH POWER FEED.

TRANSFORMERS* (ORDERED SEPARATELY)

| ITEM | DESCRIPTION | DIMMING |
|--|---|--|
| 700AT060EL 700AT152EL 700AT152ELD010 700AT150T 700AT150T277 700AT302EL 700AT300T | ELECTRONIC, 60W, 120V ELECTRONIC, 150W, 120V ELECTRONIC, 150W, 120V MAGNETIC, 150W, 120V MAGNETIC, 150W, 277V ELECTRONIC, 300W, 120V MAGNETIC, 300W, 120V | ELV ELV 0-10V MAGNETIC ELV MAGNETIC |
| 700AT300T277 | MAGNETIC, 300W, 277V | MAGNETIC |

DO NOT LOAD TRANSFORMER ABOVE 70% OF RATED LOAD DUE TO IN-RUSH CURRENT. *CONSULT SPEC SHEETS FOR DIMENSIONS.

PROJECT INFO

by Tech Lighting" GENERATION BRANDS 7400 Linder Avenue, Skokie, Illinois 60077

T 847.410.4400 F 847.410.4500

© 2017 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.

ELEMENT-lighting.com