



REPORT

545 E. Algonquin Rd., Arlington Heights, IL 60005

Project No. G103017649

Date: December 8, 2017

REPORT NO. 103017649CHI-053

TEST OF ONE LED WALL WASH

MODEL NO. E2SF-LH83030AI W/ E2SFW-WW TRIM
LED MODEL NO. CITIZEN CLU028-1203C4-303M2M2-F1
DRIVER MODEL NO. DA18W440C40BF-0000

RENDERED TO

GENERATION BRANDS
7400 LINDER AVE.
SKOKIE, IL 60077 USA

TEST: Electrical and Photometric tests as required to the IESNA test standard.

AUTHORIZATION: The testing performed was authorized by signed quote number Qu-00779063-2.

STANDARDS USED: The following American National Standards or Illuminating Engineering Society of North America Test Guides were used in part or totally to test each specimen:

IESNA LM-79 - 2008: Electrical and Photometric Measurements of Solid State Lighting

DESCRIPTION OF SAMPLE: The client submitted one production sample of model number E2SF-LH83030AI w/ E2SFW-WW trim. The sample was received by Intertek on December 8, 2017, in undamaged condition and one sample was tested as received. The sample designation was AH12082017094601-053.

DATES OF TESTS: December 8, 2017

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



SUMMARY

Model No.: E2SF-LH83030AI w/ E2SFW-WW trim Description: LED Wall Wash
--

<u>Criteria</u>	<u>Result</u>
Total Lumen Output (Lumens)	690.2
Total Power (W)	18.81
Luminaire Efficacy (LPW)	36.69
Power Factor	0.981

EQUIPMENT LIST

<u>Equipment Used</u>	<u>Model Number</u>	<u>Control Number</u>	<u>Last Date Calibrated</u>	<u>Calibration Due Date</u>	<u>Date Used</u>
Yokogawa Power Meter	WT210	146919	07/10/17	07/10/18	12/08/17
Omega Newport Thermometer	DPI8-C24	146920	10/04/17	10/04/18	12/08/17
LSI High Speed Mirror Goniometer	6440T	146928	VBU	VBU	12/08/17
Newport Thermohygrometer	iServer	146956	01/06/17	01/06/18	12/08/17
Pacific, AC power supply	118-ACX	CHI0358	VBU	VBU	12/08/17

TEST METHODS

Seasoning in Sample Orientation – LED Products

No seasoning was performed in accordance with IESNA LM-79.

Photometric and Electrical Measurements – Distribution Method

A LSI Type C High Speed Model 6440 Mirror Goniometer was used to measure the intensity (candelas) at each angle of distribution for each sample.

Ambient temperature was measured equal to the height of the sample mounted on the Goniometer equipment. Each sample was operated at input rated voltage in its designated orientation. Each sample was allowed to stabilize for at least thirty minutes before measurements were made. Electrical measurements including voltage, current, and power were measured using the Xitron or Yokogawa Power Analyzer.

Some graphics were created with Photometrics Plus software.


RESULTS OF TEST

Photometric and Electrical Measurements at Ambient Temperature (25°C +/- 1°C) – Distribution Method

Intertek Sample No.	Base Orientation	Input Voltage {VAC}	Input Current (mA)	Input Power (Watts)	Input Power Factor	Absolute Luminous Flux (Lumens)	Lumen Efficacy (LPW)
AH12082017094601-053	UP	120.1	159.7	18.81	0.981	690.2	36.69

Intensity (Candlepower) Summary at 25°C - Candelas

Angle	0	25	45	67.5	90
0	186	186	186	186	186
5	315	307	266	219	175
10	506	466	352	243	159
15	753	671	444	253	140
20	896	770	516	254	129
25	1047	850	502	244	109
30	1120	878	468	221	82
35	1077	824	421	166	58
40	950	710	358	108	54
45	795	581	262	106	38
50	656	462	170	65	32
55	493	346	131	53	25
60	235	205	68	30	19
65	78	84	35	19	15
70	22	24	12	10	11
75	5	5	4	3	4
80	2	2	2	1	1
85	0	0	0	0	0
90	0	0	0	0	0




RESULTS OF TEST (cont'd)


Illumination Plots

Mounting Height: 10 ft.

Illuminance - Cone of Light



Isoillumination Plot




Zonal Lumen Summary and Percentages at 25°C

Zone	Lumens	% Luminaire
0-30	234.6	34.0
0-40	404.3	58.6
0-60	650.5	94.2
60-90	39.7	5.8
0-90	690.2	100.0
90-180	0.0	0.0
0-180	690.2	100.0

Zonal Lumens and Percentages at 25°C

Zone	Lumens	% Luminaire
0-10	19.5	2.8
10-20	75.3	10.9
20-30	139.8	20.3
30-40	169.7	24.6
40-50	148.2	21.5
50-60	98.0	14.2
60-70	33.2	4.8
70-80	5.8	0.8
80-90	0.7	0.1

PICTURES (not to scale)



CONCLUSION

The results tabulated in this report are representative of the actual test samples submitted for this report only. The data is provided to the client for further evaluation. Compliance to the referenced specification requirements was not determined in this report.

In Charge Of Tests:

Hector Huitron
Associate Engineer
Lighting Division

Attachment: None

Report Reviewed By:

Timothy Quigley
Engineer
Lighting Division