



REPORT

545 E. Algonquin Rd., Arlington Heights, IL 60005

Project No. G102171228

Date: April 10, 2017

REPORT NO. 102171228CHI-084

TEST OF ONE LED DOWNLIGHT

MODEL NO. E2SL-LO83030AI
LED MODEL NO. CITIZEN CLU028-1203C4-303M2M2-F1
DRIVER MODEL NO. LTF DA15W300C2042BF-00HE

RENDERED TO

GENERATION BRANDS
7400 LINDER AVE.
SKOKIE, IL 60077 USA

TEST: Electrical and Photometric tests as required to the IESNA test standard.

AUTHORIZATION: The testing performed was authorized by signed quote number 500606081.

STANDARDS USED: The following American National Standards or Illuminating Engineering Society of North America Test Guides were used in part or totally to test each specimen:

IESNA LM-79 - 2008: Electrical and Photometric Measurements of Solid State Lighting

DESCRIPTION OF SAMPLE: The client submitted one prototype sample of model number E2SL-LO83030AI. The sample was received by Intertek on April 4, 2017, in undamaged condition and one sample was tested as received. The sample designation was 04042017041733B.

DATES OF TESTS: April 10, 2017

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

SUMMARY

Model No.:	E2SL-LO83030AI
Description:	LED Downlight

Criteria	Result
Total Lumen Output (Lumens)	1044
Total Power (W)	12.46
Luminaire Efficacy (LPW)	83.79
Power Factor	0.980

EQUIPMENT LIST

Equipment Used	Model Number	Control Number	Last Date Calibrated	Calibration Due Date	Date Used
Yokogawa Power Meter	WT210	146919	07/11/16	07/11/17	04/10/17
Omega Newport Thermometer	DPI8-C24	146920	10/07/16	10/07/17	04/10/17
LSI High Speed Mirror Goniometer	6440T	146928	VBU	VBU	04/10/17
Newport Thermohygrometer	iServer	146956	01/06/17	01/06/18	04/10/17
Pacific, AC power supply	118-ACX	CHI0358	VBU	VBU	04/10/17

TEST METHODS

Seasoning in Sample Orientation – LED Products

No seasoning was performed in accordance with IESNA LM-79.

Photometric and Electrical Measurements – Distribution Method

A LSI Type C High Speed Model 6440 Mirror Goniometer was used to measure the intensity (candelas) at each angle of distribution for each sample.

Ambient temperature was measured equal to the height of the sample mounted on the Goniometer equipment. Each sample was operated at input rated voltage in its designated orientation. Each sample was allowed to stabilize for at least thirty minutes before measurements were made. Electrical measurements including voltage, current, and power were measured using the Xitron or Yokogawa Power Analyzer.

Some graphics were created with Photometrics Plus software.


RESULTS OF TEST

Photometric and Electrical Measurements at Ambient Temperature (25°C +/- 1°C) – Distribution Method

Intertek Sample No.	Base Orientation	Input Voltage {Vac}	Input Current (mA)	Input Power (Watts)	Input Power Factor	Absolute Luminous Flux (Lumens)	Lumen Efficacy (LPW)
04042017041733B	Up	120.0	105.9	12.46	0.980	1044	83.79

Intensity (Candlepower) Summary at 25°C - Candelas

Angle	0	22.5	45	67.5	90
0	3365	3365	3365	3365	3365
5	2986	3062	3112	3181	3249
10	2345	2407	2492	2589	2687
15	1427	1511	1679	1780	1870
20	686	746	921	944	1006
25	273	306	357	418	440
30	80	108	125	165	148
35	25	34	56	52	40
40	6	8	23	14	10
45	2	3	6	4	3
50	1	1	2	1	1
55	0	0	1	0	0
60	0	0	0	0	0
65	0	0	0	0	0
70	0	0	0	0	0
75	0	0	0	0	0
80	0	0	0	0	0
85	0	0	0	0	0
90	0	0	0	0	0




RESULTS OF TEST (cont'd)


Illumination Plots

Mounting Height: 10 ft.

Illuminance - Cone of Light



Isoillumination Plot





Zonal Lumen Summary and Percentages at 25°C

Zone	Lumens	% Luminaire
0-30	997.6	95.5
0-40	1038	99.4
0-60	1043	99.9
60-90	0.9	0.1
0-90	1044	100.0
90-180	0.0	0.0
0-180	1044	100.0

Zonal Lumens and Percentages at 25°C

Zone	Lumens	% Luminaire
0-10	286.8	27.5
10-20	493.1	47.2
20-30	217.7	20.8
30-40	40.3	3.9
40-50	5.0	0.5
50-60	0.6	0.1
60-70	0.4	0.0
70-80	0.3	0.0
80-90	0.2	0.0

PICTURES (not to scale)



CONCLUSION

The results tabulated in this report are representative of the actual test samples submitted for this report only. The data is provided to the client for further evaluation. Compliance to the referenced specification requirements was not determined in this report.

In Charge Of Tests:

Jehue Williams
Associate Engineer
Lighting Division

Attachment: None

Report Reviewed By:

Timothy Quigley
Engineer
Lighting Division