

Innovative, first-of-its-kind technology in architectural downlights, ELEMENT Reflections Remodel combines decorative recessed domes with beautifully controlled, reduced-glare indirect LED illumination. ELEMENT Reflections Remodel domes (available in 5", 8" and 12" diameters) are recessed into the ceiling plane and act as reflectors to a completely hidden ring of up-firing LEDs.

The Skye dome transforms beautiful three-dimensional geometry for dramatic visual interest with the subtle play of light and shadow. All ELEMENT Reflections domes also offer two ceiling appearance options: flanged for a more traditional ceiling appearance; or flangeless for a smooth, mudded-in ceiling appearance.

Pristine design and illumination:

- Reduced glare, indirect illumination (dimnable for enhanced mood-setting options)
- Three Aperture Options: 5", 8" and 12"
- Beveled, rounded trim edges smoothly and seamlessly integrate into ceiling

High quality LM80-tested LEDs

for consistent long-life performance and color

SPECIFICATIONS

DELIVERED LUMENS	5":	684
	8":	1255
	12":	1989
WATTS	5":	9
	8":	15
	12":	31
VOLTAGE	Universal 120V-277V	
DIMMING*	0-10V, ELV, TRIAC, Eco-system, Dali	
POWER SUPPLY	Constant current driver with +.9 power factor and +85% efficiency	
LIGHT DISTRIBUTION	Lambertian	
CCT	2700K, 3000K, 3500K, or Warm Color Dimming (3000K-2000K)	
CRI	90+	
CEILING APPEARANCE	Flanged (Trims accommodate a 1/2" to 1" ceiling thickness) or Flangeless with integrated mud plate	
HOUSING	IC	
GENERAL LISTING	ETL listed, Damp listed	
CALIFORNIA TITLE 24	Registered CEC Appliance Database. Can be used to comply with CEC 2016 Title 24 Part 6.	
LED LIFETIME	L70; 50,000 Hours	
WARRANTY*	5 Years	

*Visit ELEMENT-lighting.com for specific details.



SKYE
shown in flanged




SKYE
shown in flangeless

ORDERING INFORMATION


PRODUCT SERIES	CEILING APPEARANCE	CRI/CCT	DOME	HOUSING RATING	DIMMABLE DRIVER	FINISH
EDIM5R	RL REMODEL FLANGELESS	927 90 CRI, 2700K	1 SKYE	I IC	ELV/TRIAC/0-10V UNV**	W WHITE
EDIM8R	RF REMODEL FLANGEDV	930 90 CRI, 3000K			-ELD0 ELDOLED 0.1% 0-10V LINEAR UNV**	
EDIM12R		935 90 CRI, 3500K			-ELD0A ELDOLED 0.1% 0-10V LOGARITHMIC UNV**	
		WD 90 CRI, WARM DIM 3000K-2000K			-ELD1 ELDOLED 1% 0-10V LINEAR UNV**	
					-ELD1A ELDOLED 1% 0-10V LOGARITHMIC UNV**	
					-ELDD ELDOLED 0.1% DALI UNV**	
					-HLECO HI-LUME ECO-SYSTEM FADE-TO-BLACK UNV**	
					-HL2W HI-LUME 2 WIRE - 120V ONLY*	

*HL2W - 120V INPUT VOLTAGE ONLY. **ALL DRIVERS EXCEPT LUTRON HL2W ARE UNV = 120V/277V INPUT VOLTAGE.


DOMES/TRIM




Skye Flanged 5"




Skye Flanged 8"




Skye Flanged 12"



Skye Flangeless* 5"
*shown with plaster plate




Skye Flangeless* 8"



Skye Flangeless* 12"


DOMES/TRIM WITH REMOTE JUNCTION BOX




Flanged 5"

Flangeless 5"

J-Box (side view/top view)




3/4 Flanged View




Flanged 8"

Flangeless 8"

J-Box (side view/top view)



3/4 Flangeless View with integrated mud plate



Flanged 12"

Flangeless 12"

J-Box (side view/top view)

PHOTOMETRICS*

*For latest photometrics, please visit www.ELEMENT-Lighting.com

SKYE 5"




Total Lumen Output: 684
 Total Power: 9
 Luminaire Efficacy: 76
 Color Temp: 3000K
 CRI: 90+

SKYE 8"

Total Lumen Output: 1255
 Total Power: 15
 Luminaire Efficacy: 84
 Color Temp: 3000K
 CRI: 90+

SKYE 12"

Total Lumen Output: 1989
 Total Power: 30.8
 Luminaire Efficacy: 64
 Color Temp: 3000K
 CRI: 90+



PROJECT INFO

FIXTURE TYPE & QUANTITY

JOB NAME & INFO

NOTES



2019 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark. Tech Lighting reserves the right to change specifications for product improvements without notification.

TECH LIGHTING
 VISUAL COMFORT GROUP

7400 Linder Avenue, Skokie, Illinois 60077
 T 847.410.4400 F 847.410.4500